Summit Architectural
Complete plywood and panel solutions

JOINERY PLY

Hoop Pine Plywood

CHARACTERISTICS

Hoop plywood is from100% plantation grown forests.
Hoop Pine is a brighter light cream colour that has a more consistent grain pattern than Radiata.
A Rotary cut softwood, it's extremely popular in Architectural linings, particularly large ceiling areas.
Hoop also has an excellent multiply edge-detail that is suitable for many joinery applications.

USES

Specialist Furniture
Wall and Ceiling linings
Joinery, Kitchen fit-outs
Feature panels and both Domestic and Commercial cabinetry.

SPECIFICATIONS

Sheet Size	Sheet Thickness	Weight	Grading
2400x1200 Interior	1.5mm, 6mm, 16mm, 19mm and 25mm	600 kg/m3	AC or AA
2400x1200 A Bond	9.5mm, 12.5mm, 18.5mm and 25mm	600 kg/m3	AC
2700 length sheets on request.			

Material	Light cream, Australian softwood with fine grain texture. Multiply lay-up(A-Bond sheet)
Glue Bond	A-Bond exterior
Certification	FSC 100%, Interior also AFS and PEFC sourced
Emissions	Meets E0 spec of AS/NZS 2271, Full certification pending
Plantation Source	Queensland, plantation grown

HANDLING & APPLICATION INFORMATION

Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content temperature variation may cause internal stresses causing previously flat sheets to bow. This is particularly applicable to Hoop ply as it is a softwood timber.
At Summit precautions are taken to minimize this effect. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened.
This is very important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

For further information, contact our dedicated, trained sales staff.
North Island 06 344 1126
Christchurch 03 928 1520

Freephone 0800 344 112
E sales@summitply.co.nz **F** 06 344 1129
www.summitply.co.nz