Summit Architectural
Complete plywood and panel solutions

JOINERY PLY

Veneer Panels

CHARACTERISTICS

Beautiful, Natural Veneered Panels are available in 42 different species. With Summits experience you can specify colour and grain matching, cross or long grain layup, and a choice of substrates such as Birch plywood or FR MDF. Choice of veneer cut (1/4 cut is straighter grain and Crown cut is swirlier) is also available in some species. White Oak & Walnut come with a planked option.

USES

Architectural linings and Ceilings
Kitchen Cabinetry
Commercial & Hospitality Furniture
Paneling
Marine Interiors

SPECIFICATIONS

Sheet Size	Sheet Thickness	Weight	Grading
2440x1220 veneer on MDF	5mm, 6, 7,10, 13, 17, 19, 26 and 31mm.		FA, FB or FF
2440x1220 on MDF (MR/EO)	13mm, 17mm, 19mm, 26mm, 31mm		FA, FB or FF
2740x1220 on MDF	13mm,16mm,19mm, 26mm, 31mm		FA, FB or FF
2440x1220 on BIRCH ply	10mm, 13mm,16mm,19mm, 25mm		FA, FB or FF
2440x1220 on Gaboon ply	5mm,10mm, 13mm,16mm,19mm, 25mm		FA, FB or FF
2440x1220 on FR MDF	13mm (FIRE RATED)		FA, FB or FF
2740x1220 on FR MDF	13mm (FIRE RATED)		FA, FB or FF

NZ	NZ Silver Beech, Pine CC, Rimu (Nat.,Colour, Pale or Heart), Macrocapa, Tawa
Australia & Pacific	Fiji Kauri, Eucalyptus Oak 1/4, Eucalyptus CC or 1/4, Hoop, Blackwood CC
	Sydney Blue Gum, Spotted Gum, Jarrah
International	American White Oak CC or 1/4, Sapele 1/4 or CC, Red Oak, Amer White Ash, Walnut
	Anegre CC or 1/4, Amer Maple, Cherry, Oregon, Euro Birch, Silky Oak, Wenge

HANDLING & APPLICATION INFORMATION

Veneers require specialist lacquer protection, and requires skilled tradesman to create your natural timber project. Use UV inhibitors from a reputable coating supplier if the panels are to be exposed to sunlight. Ideally, exposure to UV is not recommended as timber does fade, especially when dark timbers are used. Veneer panels are a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content & temperature variation may cause internal stresses causing previously flat sheets to bow. At Summit precautions are taken to minimize this effect. However, once panels have left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is very important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

For further information, contact our dedicated, trained sales staff.
North Island 06 344 1126
Christchurch 03 928 1520

Freephone 0800 344 112
E sales@summitply.co.nz **F** 06 344 1129
www.summitply.co.nz