Summit Architectural
Complete plywood and panel solutions

ENVIRONMENTAL

Pureply Maple

CHARACTERISTICS

Pureply Maple has total formaldehyde FREE glue. Replacing traditional glues with Soy base resins this is environmental winner! With a premium core and beautiful Maple veneers Pureply is excellent in both cabinetry & linings.

USES

Decorative Linings
Cabinetry and Kitchens
Furniture
Architectural fit outs

SPECIFICATIONS

Sheet Size	Sheet Thickness	Weight	Grading
2440x1220	6mm, 9mm, 12mm,	apx 500kg/m3	AC
2440x1220	18mm & 25mm	apx 500kg/m3	AB
3000mm sheets manufactured on			
request			

Material	AC Maple Hardwood Veneer, N.A. Poplar Core lay-up/Light Pink with a straight grain
Glue Bond	Soy - based Resin, Formaldehyde Free
Certification	FSC, Phase 2 Carb. Certification
Emissions	E0, "Passed" VOC Emission Test, BERKELEY ANALYTICAL ASSOCIATES, LLC
Plantation Source	North American Maple veneers & N.A. plantation Poplar veneers

HANDLING & APPLICATION INFORMATION

Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content temperature variation may cause internal stresses causing previously flat sheets to bow. At Summitply, precautions are taken to minimise this effect. However, once the plywood has left our warehouse we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.

For further information, contact our dedicated, trained sales staff.
North Island 06 344 1126
Christchurch 03 928 1520

Freephone 0800 344 112
E sales@summitply.co.nz **F** 06 344 1129
www.summitply.co.nz